

TRMM Monthly Status Review Briefing

November 1st, 2000



FOT Overview

- Operations Status Engineering Staff
 - Flight Ops Summary Lou Kurzmiller
 - Electrical & Thermal Andy Calloway
 - ACS & FDS / C&DH Mark Fioravanti
 - RCS & RF / Comm David Corley for Rob Bote
 - Power & Deployables Justin Knavel
 - CERES & VIRS Mark Fioravanti
 - LIS, TMI, & PR Andy Calloway
 - Ground System Andy Calloway
 - Upcoming Activities Andy Calloway
 - Leonids Timeline Overview Andy Calloway



Flight Operations Summary

- Supported 554 SN events in October
 - 2 Yaw Maneuvers
 - 12 Delta-V Maneuvers
- 5 Event Rpts & 1 Generic Late Acq Rpt generated
 - ER #209 & #210: EPV Continuity
 - ER #211: Receiver 1 Dropout
 - ER #212: LTS Line Configuration
 - ER #213: 2 Events Taken due Critical ISS



Flight Operations Summary

- Notable Events
 - Spacecraft PWR subsystem configured to preferred state
- Staffing
 - 1 subsystem engineer completed Certification

FOT - Page 4 TRMM MSR - November 1st, 2000



Flight Ops Summary

SPECIAL EVENTS AND ACTIVITIES FOR TRMM 2000													
	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	TOTALS
2	6	8	10	13	9	7	9	8	8	12			90
2a	1	1	2	1	1	1	2	1	1	2			13
2b	0	0	0	0	0	0	0	0	0	0			0
2c	0	0	0	0	0	0	0	0	0	0			0
3	2	1	0	1	2	2	2	2	1	1			14
3a	5	1	3	7	4	4	2	4	6	9			45
3b	3	1	2	4	4	3	3	6	3	3			32
3c	0	3	2	2	0	0	2	0	2	2			13
3d	1	0	1	0	0	0	0	0	1	1			4
3e	0	0	0	0	0	0	0	0	44	0			44
3f	6	1	3	3	5	2	2	4	3	1			30
4	3	3	0	3	3	5	0	2	1	1			21
4a	2	2	2	2	2	2	2	2	2	2			20
4b	1	2	2	1	2	1	1	2	1	2			15
4c	0	7	21	23	10	19	12	3	1	0			96
4d	11	0	4	1	4	2	4	1	2	4			33
4e	0	0	0	0	0	0	0	0	0	0			0
5	26	6	4	5	16	11	9	5	6	16			104
5a	0	0	4	0	1	4	2	0	0	0			11
5b	3	3	2	3	0	0	2	1	2	4			20
5c	0	0	0	0	0	0	0	0	0	0			0
8	0	0	0	0	0	0	0	0	0	0			0
8a	0	0	0	0	0	0	0	0	0	0			0
гот:	70	39	62	69	63	63	54	41	84	60	0	0	605
							LEGI	END					
CSOC CATEGORIES				TRMM SUB-CATEGORIES AND EXAMPLES									

Targets of Opportunity N/A DeltaVs (2) , 180° Yaw Maneuvers (2a) , 90° Yaws (2b) , Deep Space Cals (2c) S/C Maneuvers Blind Acqs (3), Patch Loads (3a), Manual DS Ops - Blind Acqs, MI, H/W Problems (3b) . EPV Fail Ops (3c) Unplanned Events (3d) , Anomaly Recoveries (3e) , Generic Late Acqs - GCMRs and Manual DS Ops VIRS Reset Recoveries (3f) Customer Requests PR (4) , VIRS (4a) , LIS (4b) , CERES (4c) , FSW (4d) , AETD (4e) Celestial Phenomena VIRS Heater Ops (5) , Power Ops - Autospru, TSMs, C/D (5a) , UTCF / FS Ops (5b) , Leonids Ops (5c) Pre-Launch Testing N/A L&IOC Operations N/A **EOL Operations** Delta-H Firings (8) , Reentry Maneuvers (8a)



Thermal / Electrical Subsystems

- Thermal and Electrical subsystems remain nominal with no open issues
- FOT will assist AETD as needed for End Of Life Thermal Analysis
 - Who will be the AETD Point of Contact Kim Brown?
 - What is lowest attainable perigee which still meets thermal survivability constraints?
 - What are the thermal constraints, if any, of long duration burns with respect to non-thruster spacecraft components?

FOT - Page 6 TRMM MSR - November 1st, 2000



ACS Subsystem

- Open CCRs (In order of Priority);
 - CCR #069: New table 85 to match new TDRS-8 continuity limits for other TDRS, and another table 85 to widen the limits after an update failure.
 - CCR #070: New version of Table 61 to incrementally pitch the S/C while in SunAcq.
 - CCR #005: Correction for Magnetic Field Epoch, will be required for EOL if apogee is greater than 400 km.
 - CCR #065: Update ACS system tables in preparation for EOL activities.
 - » Table #73 (Thruster Parameters)
 - » Table #90 (Mode Configuration Data for Contingency)
 - CCR #053: ACS FS/W bug

FOT - Page 7 TRMM MSR - November 1st, 2000



FDS/C&DH Subsystems

UTCF Status;

- Three Adjustments were performed in October. On 00-282 (Sunday, October 8th, 2000), 00-291 (Tuesday, October 17th, 2000), and 00-301 (Friday, October 27th, 2000)
- Current UTCF value is 31535996.835569 sec
- FS Adjustment was performed on 00-301 (Friday, October 27th, 2000)
- Current FS value is x'7ae'

• New CCRs:

 New TSM table to accommodate the change in operations resulting from the PSIB Anomaly (See Power Section)

FOT - Page 8 TRMM MSR - November 1st, 2000



FDS/C&DH Subsystems

• Open CCRs;

- CCR #034: Writing from RAM to EEPROM for new TSM table #21 and RTSs # 2, 3, 13, 14, and 15. Completed, only need final documentation.
- CCR #047: Will work with FSW on no-clock software patch activities
- CCR #048: New on-board DS filter table to record ACE 8-Hz data
- CCR #071: Build a new DS quota table (73) to reallocate CERES science memory to other instruments, contingent on powering CERES off permanently.

FOT - Page 9 TRMM MSR - November 1st, 2000



RCS Subsystem

- RCS performed 12 successful Delta-V maneuvers (#231 #242)
- EOL worst case remains **September**, **2003**
 - Current fuel remaining is 507.217 kg
- No Open RCS Anomaly or Event Reports
- Upcoming Events
 - Begin review of, and training in, Delta-H procedures and scripts for EOL

FOT - Page 10



RF Subsystem

- 1 Generic Late Acquisition (#72)
- Frequency offset Transponder #1 = +699.862 Hz (average)
- Frequency offset Transponder #2 = -821.522 Hz (average)
- 2 RF Event Reports
 - #211: 16 s receiver #1 dropout on 10/17. All data recovered.
 - #212: Late acquisition due to line misconfiguration within MOC. All data recovered.
- Performing 1/1 k events once a week for training/risk reduction
- No new RF MOCRs this month
- Upcoming Events
 - Offset of transponder frequencies likely within 6 months



Power Subsystem

- No change in PSIB A and B telemetry
- 00-287(October 13th) Switched to Constant Current Mode (CCM) & VT 5 from Peak Power Tracking (PPT) & VT 4 due to concern of PPT damaging Battery #2 Cell #1.
- New RTS 21 and TSM 37 40 Testing on-going
 - If a further PSIB failure occurs, which causes the power system to charge at a low Constant Current, then RTS 21(LOADSHEDPPT) will prevent the power system from being locked in CCM by commanding to PPT, prior to additional failures. Currently, 3 failures would have to occur to be locked in low CCM.
 - RTS 21 performs the same functions as RTS 2(LOADSHED) except for the following:
 - » PPT & VT 4 instead of CCM & VT 5 (See Flowchart)
 - Two Loadshed RTSs are needed because RTS 10 & 11 (BATOFF) must still stay in CCM, PPT will cause extremely high current to go into 1 battery.



Power Subsystem

- The following TSMs will now call RTS 21
 - » Battery SOC < 70% (TSM 3 & 4)
 - » Essential Bus Voltage < 24.7 v (TSM 8)</p>
- New TSMs 37 40 will monitor Battery Differential Voltage Average
 - » Threshold 1 & 2 Event Message
 - » Threshold 3(+/- 700 mv) RTS 10 or 11 (BATOFF)



Power Subsystem

10/19/2000 New Low Power RTS Scenario PSIB-B Detects Bus PSIB Detects Battery Cell S/C Processor detects Low S/C Processor detects Possible S/C Processor detects high S/C Processor detects Low under-voltage Battery SOC Cell Short in Differential under-voltage Battery Temperature EOD Battery SOC PSIB-A DISABLED PSIB-A / B DISABLED TSMs 1 & 2 PSIB-A TSM 37, 38, 39, or 40 TSMs 21 & 22 PSIB-A TSMs 31 & 32 PSIB-A TSMs 3 & 4 PSIB-B PSIB-B Only & All Cells Masked PSIB-B Only TSM s 23 & 24 PSIB-B TSMs 33 & 34 PSIB-B PSIB sets "Low Power" bit in S/C RTS #10 (BATT1OFF) or RTS #11 (BATT2OFF): telemetry. Starts 95 second "back-up" timer. charge (open K1 relay) S/C RTS #21 (LOADSHEDPPT) : S/C Processor detects PSIB Timer "Low Power" bit in telemetry Disable RTS #13 TSM 7 PSIB-A Activate RTS #2 TSM 8 PSIB-B VT4 PPT RTS #13 (SPRUCONFIG) : RTS #2 (LOADSHED) : Disable Auto-SPRU . Disable NEB shutdown in the PSIB •VT5 . Command the TMM issue S/H •Gain 1 PSIB shutdown of the NEB •CCM (CM_2) 12 Amps . Activate RTS #13 (If not Disabled disabled, including stopping the By 21) PSIB timer (if active) If S/C Processor is "down" and the •Wait 92 seconds Load Shedding RTS's are not •Activate RTS #15 executed, the PSIB 95 second low •Wait 15 PR receives S/H L/P pulse and power timer will expire and the •Activate RTS #34 RTS #15 (RELAYOPEN) : commands FCIF power OFF, RF NEB will be switched off. •TMI survival heaters On •TMI - OFF power supply OFF and halts the •LIS - OFF SCDP (1 or 2 seconds) •PR - OFF •CERES - Safe Mode •VIRS - OFF CERES receives S/H L/P pulse •RCS high press transducer - OFF and safes itself (less than 10 seconds) Note: Currently all TSMs relying on PSIB-A telemetry are VIRS receives S/H L/P pulse and RTS #34 (CERESSURV) : DISABLED. closes doors (up to 90 seconds) •CERES to Safe Mode •CERES OFF



Deployables Subsystem

- Solar array drives and HGA continue to operate nominally
- No open issues other than to concentrate on array behavior and contingency training with all FOT members



CERES Instrument

- Power On will be attempted on or about 00-350 (December 16th, 2000)
- Open Issues
 - Data Acquisition Processor (DAP) Telemetry Drop Out and Possible Failure (Anomaly #81)
- Issues on Hiatus
 - Continuous Biaxial operations
 - DR on MP ground system to incorporate new CERES requirements



VIRS Instrument

- 2 Solar Calibrations were performed on 00-298 (Tuesday, October 24th, 2000)
- VIRS performed self reset #14 on 00-291 at 14:19:09z (Tuesday, October 17th, 2000)



LIS Instrument

- Routine MSFC real-time command request performed on 00-285 and 00-298 (October 11th and 24th) to reduce packet sequence errors
- No open issues



TMI / PR Instruments

- No concerns or open issues for TMI
- PR Activities:
 - LNA Analysis command request performed on October 19th (00-293)
- PR Open Issues
 - Frequency Agreement Renewal
 - » No new interference reported in October



Ground System

- PTPs now have redundant power supply failover capability to allow seamless transfer between UPS-5 (primary) and UPS-2 whenever one of them goes down
- UPS-5 outage is still scheduled for November 14th FOT operational timeline of activities has been completed
 - Events will be supported on String -2 (UPS-2) during the outage with no failover capability
- Work Request to move MOR air vents has been submitted



Upcoming Activities

• 0-2 Months

- Ensure FOT training remains top priority
- Continue PSIB-Anomaly investigation and activities
- Power the CERES instrument back on
- Leonids Operations (11/18/2000)
- New FDF Product deliveries which will incorporate new TDRS-8 data
- New System Software Release which will support TDRS-8
- Completion of TRMM/XTE MOC failover implementation
- Continue to close open CCRs, MOCRs, ERs, ARs, and MSR Action Items

FOT - Page 21 TRMM MSR - November 1st, 2000



Upcoming Activities

• 2-3 Months

- Begin testing and using the new TDRS-8
- Leap Year Transition for DOY 366 No Leap Second Adjustment

• 3-12 Months

- Extended Mission Operations (1/2000)
- Test, validate, and accept the new PACOR-A system
- Begin End Of Life Planning, Testing, and Simulations
- Commence DSN/GN FOT training
- Testing of new PTP hardware and software deliveries
- System Software Release 8.2 Delivery
- Transponder Offset Activities